



STANDARD SET

ADD MIX

Enhances Flexibility &
Durability of Cementitious Grout



Product Description

ADD MIX (Cementitious Colour Grout) is liquid polymer admixture for used to improve the quality of cement grouts, It is ideal for interior and exterior tile grout application and enhances flexibility & durability to have better performance. Specially designed for use with Colorfast Grout.

Special Features & Standard Followed

- Reduce water absorption
- Improve the compressive strength
- Increase the abrasion resistance of grout
- Inhibits Powdering and Cracking of Cement Grout
- Exceptional colour – stability
- Wide joint bridging (Up to 5 mm)
- Flexible to with—stand pressures created by expansion and contraction of joints tiles
- Non—shrinkable and will not crack
- Reduces Problems with colour fading in grouts

Application

- Bathrooms
- Wall & Floor
- Kitchens
- Interior & Exterior

Suitable Substrates

- Porous and absorbent type joints tile
- Marble & Glazed wall joints tiles
- Non—vitreous clay joints tiles
- Glass Mosaic joints tiles

Technical Properties

Testing Parameters	Result	Testing Parameters	Result
Appearance	Milky White Colour Liquid	Time to Heavy Traffic	72 hours
Mixing Ratio	300 – 400 ml of for Grout (1kg)	Linear Shrinkage	< 0.15%
	10 – 15% for Adhesive	Compressive Strength (28 days)	8 N / mm ²
Pot Life	1 hour	Tensile Strength (28 days)	≥ 1 N / mm ²
Cleaning Time	30 minutes	Flexural Strength (28 days)	≥ 7 N / mm ²
PH	8 – 10	Water Absorption	5 – 10%
Time to foot Traffic	24 hours		

Packing

200ml, 500ml. 1 litre & 5 litre

Shelf Life

Factory sealed packs are best before 12 months from the date of manufacturing in unopened condition and stored in cool & dry area.