



STANDARD SET BOND LATEX

High Performance SBR Latex For
Waterproofing



Product Description

BOND LATEX is modified Styrene Butadiene Rubber based Multipurpose and high quality Latex, It is in liquid consistency and can be utilized as a Bonding Agent, as Quality Enhancer in Repair Mortar, as a good waterproofing agent and as Primer coating in Cementitious applications. It is ideal to apply internal and external applications to intermix with cement.

Special Features & Standard Followed

- Excellent adhesion to cement mortar and tile adhesives as a bond coat
- Very good bonding agent to old and new concrete surfaces
- Improve flexural strength thus prevent cracking
- Excellent waterproofing properties

Application

- Suitable for repair mortar for repairing of old & new concrete structure
- As an Excellent mortar and tile adhesive quality improver
- Very good as Cement mortar quality enhancer
- Suitable as an excellent bonding agent
- Suitable as bonding agent in under coat cementitious applications
- Suitable as a very good waterproofing agent
- Suitable for waterproofing of small roof, toilets, bathrooms and balconies

Suitable Substrates

- Interior and Exterior surface
- Old and new concrete surface
- All Cementitious, concrete and masonry surfaces

Technical Properties

Testing Parameters	Result
Appearance	Milky White Colour Liquid
Pot Life	45 - 50 minutes
Specific gravity	1.01 ± 0.01 gm/ml
Solid content	32 ± 2 %
Resistance to Water Pressure	2 Bar
Mixing Ratio (BOND LATEX : CEMENT)	1 : 1.5 to 2 kg

Coverage

Approx. 20 to 25 sq. ft / Ltr / 2 Coats

Packing

200ml, 500 ml, 1 ltr, 5 ltr, 10 ltr, 20 ltr, 50 ltr, 100 ltr & 210 ltr

Shelf Life

Factory sealed packs are best before 24 months from the date of manufacturing in unopened condition and stored in cool & dry area.