



STANDARD SET

BOND SBR 100

High Performance SBR For
Repairs & Waterproofing



Product Description

BOND SBR 100 is high quality SBR based liquid for high performance applications is waterproofing and repairs. It is suitable as an admixture for obtaining waterproof concrete, plasters & mortars.

Special Features & Standard Followed

- IS 15477: 2019
- Adhesive to improve the adhesion to various substrates
- Improve the deformability and Impermeability
- Improve the compressive strength
- Suitable for internal & external application
- Makes high strength shock resistant adhesive
- Increases the qualities of cement mortar, concrete
- Sag resistant

Application

- Cement mortar, Concrete & screeds
- Can be used for old to new concrete substrate by bonding mortar
- Cement backer board
- Gypsum Wallboard
- Cement Terrazzo

Technical Properties

Testing Parameters	Result
Appearance	Milky White Colour Liquid
Mixing Ratio (BOND SBR 100 : WATER : CEMENT)	1 : 4 : 7
Solids	≥ 42%
Water Resistance	Up to 3 bar pressure
Bonding Strength	≥ 4 N / mm ²
Tensile Strength	≥ 3 N / mm ²
pH	7 ± 1
Specific Gravity	1.02 ± 0.02 gm/ml

Coverage

Approx. 70 to 80 sq. ft. / Ltr / 2 Coats

Packing

200ml, 500 ml, 1 ltr, 5 ltr, 10 ltr, 20 ltr, 50 ltr, 100 ltr & 210 ltr

Shelf Life

Factory sealed packs are best before 24 months from the date of manufacturing in unopened condition and stored in cool & dry area.

