



STANDARD SET

COLOURFAST GROUT

Cementitious Polymer Colour Grout



Product Description

COLOURFAST GROUT (Cementitious Colour Grout) is white cement based, polymer modified colour grout. It is right bonding materials to fill tile joints to fix ceramic & vitrified tiles on walls and floors. They are resistant to shrinkage and cracking and can be used to fill tile joints (walls and floors) with a minimum width of 1 to 5 mm for both interior and exterior applications. Made with colour fast pigments and fine graded aggregates. It is available in more than 20 colours to match your joints with tiles.

Special Features & Standard Followed

- Resistance to shrinkage and cracking
- Suitable to fill joints at wall and floor to fix glass mosaic, ceramic & vitrified tile
- Suitable for stone material (natural stones, marbles, granite, agglomerates etc.)
- Exceptional colour stability
- Flexible to withstand pressure created by expansion and contraction of tiles

Application

- Specially for interior & exterior floor & wall
- Washrooms and cleaning rooms
- Swimming pools
- Hospitals and Operation Theatres
- Schools
- Lounges

Suitable Substrates

- Porous and absorbent type tiles
- Non-vitreous clay tiles
- Stone material (Natural stones, Granite, Agglomerates etc.)
- Marble 8L Glazed wall tiles
- Glass mosaic tiles

Technical Properties

Testing Parameters	Result	Testing Parameters	Result
Joint with	1 to 5 mm	Time to Heavy Traffic	7 days
Mixing Ratio	300 - 350 ml of water for 1Kg	Linear Shrinkage	0.25 %
Pot Life	60 - 90 minutes	Compressive Strength (28 days)	6 N/mm ²
Initial Water Cleaning	1 - 2 hours	Tensile Strength (28 days)	1.5 N/mm ²
Time to Foot Traffic	24 hours	Flexural Strength (28 days)	2 N/mm ²

Packing

500 gm & 1 kg

Colour

Available in more than 20 shades

Coverage

Varies with width & depth of joint

Factory sealed packs are best before 12 months from the date of manufacturing in unopened condition and stored in cool & dry area.