



STANDARD SET

COLOURFAST EPOXY

Three Component Epoxy Grout



Product Description

COLOURFAST EPOXY (Epoxy Stain—free Grout) is three component epoxy grout, designed specially for use in filling up joints of ceramic tiles, vitrified tiles and joints, where hygiene is of utmost importance. SET COLOURFAST EPOXY is easy to apply and recommended for internal floor & wall applications, It is chemical resistant joint filler and is available in more than 30 shade.

Special Features & Standard Followed

- Conforms to **EN 13888** : Classified RG
- Colour—fast & 100% Stain free
- High Abrasion Resistance
- Chemical resistant with non—toxic properties
- Anti—bacterial & Anti—Fungal
- Strong, Durable & Easy to Clean
- Ideal for Waterproof Grouting
- Highly resistant to Heavy Traffic
- Food Grade : CFTRI Approved

Application

- Washrooms and cleaning rooms
- Swimming Pools
- Laboratories
- Schools
- Hospitals and operation theatres
- Lounges / Restaurants / Cafeterias
- Shopping Malls
- Showrooms
- Covered exterior applications

Suitable Substrates

- Porous and absorbent type tiles
- Ceramic and vitrified tiles
- Non—vitreous clay tiles
- Granite, marble & glazed wall tiles.
- Agglomerates (Engineered Stone)
- Glass mosaic tiles
- Metallic tiles

Technical Properties

Testing Parameters		Testing Parameters	
Result		Result	
Colour	Available in more than 30 shades	Time to Foot Traffic	24 hours
Joint with	2 to 12 mm	Time to Heavy Traffic	72 hours
Pot Life	60 minutes	Temperature Resistance	-10° to 80° C
Initial Water Cleaning	60 minutes	Initial Setting Time	5 hours



Coverage

Varies with width and depth of joint.

Colour

Available in more than 30 shades

Packing

1 kg & 5 kg

Shelf Life

Factory sealed packs are best before 12 months from the date of manufacturing in unopened condition and stored in cool & dry area.