



STANDARD SET

COLOURFAST GLITTER EPOXY

Three Component Glitter Epoxy Grout



Product Description

COLOURFAST GLITTER EPOXY (Epoxy Stain-free Grout) is three component epoxy base tile grout designed specially for floor & wall areas where sparkling effect, metallic finish of aesthetics is of utmost importance such as hotels, restaurants, kitchens, showrooms, living room, swimming pool & shopping malls. SET COLOURFAST GLITTER EPOXY Grout is easy to apply and recommended for internal floor wall applications. It is easy to mix joints filler and available in more than 27 shades in Gold, Silver and Copper finish. It is particularly recommended for glass mosaic & metallic tiles.

Special Features & Standard Followed

- Conforms **EN 13888** : Classified RG
- Provides sparkling effect finish
- Colour—fast & 100% Stain free
- High Abrasion Resistance
- Chemical resistant with non—toxic properties
- Antimicrobial properties
- Strong, Durable & Easy to Clean
- Ideal for Waterproof Grouting
- Highly resistant to Heavy Traffic

Application

- Swimming Pools
- Lounges
- Restaurants & Hotels
- Showrooms
- Residential & Commercial

Suitable Substrates

- Porous and absorbent type tiles
- Ceramic and vitrified tiles
- Non—vitreous clay tiles
- Granite, marble & glazed wall tiles
- Agglomerates (Engineered Stone)
- Glass mosaic tiles
- Metallic tiles

Technical Properties

Testing Parameters	Result	Testing Parameters	Result
Colour	30 shades in Gold, Silver & Copper finish	Time to Foot Traffic	24 hours
Joint with	2 to 12 mm	Time to Heavy Traffic	72 hours
Pot Life	50 minutes	Temperature Resistance	-10° to 80° C
Initial Water Cleaning	35 minutes	Initial Setting Time	5 hours



STAIN
RESISTANT



SHRINKAGE
FREE



EASY TO
APPLY



ANTI
FUNGAL



ANTI
BACTERIAL

Coverage

Varies with width and depth of joint.

Shelf Life

Factory sealed packs are best before 12 months from the date of manufacturing in unopened condition and stored in cool & dry area.

Colour

Available in Gold, Silver & Copper finish.
Available in 30 shades.

Packing

750 gm & 3.75 kg
(250 gm resin kit + 500 gm filler powder)
(1.250 kg resin kit + 2.5 kg filler powder)