



STANDARD SET

CRACK-X

Acrylic Crack Filler Powder



► Product Description

CRACK-X is single component cement based crack filling compound, it is formulated & modified for non-shrink cementitious compositions for filling cracks in concrete, masonry & plaster surfaces and it is easy to apply and can be finished or smoothened with a putty blade/damp sponge. It sets quickly on application and can be over coated with common paints/coatings.

► Special Features & Standard Followed

- Strong adhesion to common building materials
- Excellent crack filling ability
- Non-sagging, solvent free composition
- Self-levelling
- Easy to use, ready-mixed formula

► Suitable Substrates

- It is ideal for filling and repairing concrete, masonry and cement plaster cracks,
- Roof tops
- Balconies & Decks,
- Terraces
- Walls

► Application

- Internal & External Plastered brick masonry wall cracks. (Max. up to 5mm width)

► Technical Properties

Testing Parameters	Result
Appearance	Grey & White Powder
Mixing Ratio (Powder : Water)	100 : 35
Pot Life	30 minutes
Setting Time	3 - 4 hour
Specific Gravity	1.35 - 1.45 g/cc
Compressive Strength	> 20 MPa in 28 days

► Packing

1 Kg & 5 Kg & 20 Kg

► Shelf Life

Factory sealed packs are best before 12 months from the date of manufacturing in unopened condition and stored in cool & dry area.

