



STANDARD SET

GREEP FIXX

Tiles & Stone Adhesive Retains
Better Bonding Strength



Product Description

GREEP FIXX is single component highly flexible and permanent bonding strength which use for all types of tiles, natural marbles, granite stones and synthetic / engineered stone for interiors as well as exterior surfaces. SET GREEP FIXX is suitable for absorbent as well as non absorbent surfaces.

Special Features & Standard Followed

- Higher bonding and adhesion strength
- Avoids fungus growth
- Neat and clean bonding guaranteed
- High flexibility to counteract thermal stresses
- Very economical on account of the thin-bed method
- Allows for correction of tiles within a setting period

Application

- Fixing of tiles & stones on floors, walls or overhead areas
- Bonding of heavy marble, granite and stone slabs for exterior cladding
- Fixing of tiles on existing tile surface
- For fixing tiles in interior as well as exterior areas
- Suitable for absorbent as well as non absorbent surfaces
- Fixing of tiles on surfaces like slab, plaster, marine plywood and various other surfaces

Suitable Substrates

- Ceramic Tiles, Vitrified Tiles, Glass Mosaic and Large size tiles
- Artificial stone / Engineered stones, Granite stones & Natural marbles
- All absorbent surfaces
- All Non-absorbent surfaces
- All Non-absorbent surfaces
- Tiles on existing tile surface
- Tiles on Marine plywood surface

Technical Properties

Testing Parameters	Result
Appearance	Off White-Paste
Mixing Ratio	Easy to Mix - Single Component
Application Temp. range	Minimum +20C
Pot Life	25 Minutes
Setting Time	2 Hours
Foot Trafficable Time	24 Hours

Coverage

Approx. 2 kg /m² (at approx. 1 mm thick)

Shelf Life

Factory sealed packs are best before 6 months from the date of manufacturing in unopened condition and stored in cool & dry area.

Packing

1 Kg, 5 Kg & 20 Kg